
I'm not a robot  reCAPTCHA
[Privacy](#) [Terms](#)

Continue

Ansi B 92.1 Pdf 30

30 years from the author's experiences. ... USA ANSI B 92.1. 24. 2.2. National ... 3.1.1.3. National and international standards. 30. 3.1.2. Content of standards. 31. ... 30. 32. 3. 34. 36. 38. 40. 42. 60 lo. 100. 45. 50. 50. 55. 5/10. 6/12. 8/16. 10/20 ... b These are clearance dimensions and do not require close tolerances... (e.g. ANSI 150 or 150lb). This standard ... Outside Diameter of Flange. A. Forged or Plate. Thickness of Flange. Min. B. ... 30. M27. -, -, -, -, -. *Flanges less than 12 mm thickness may suffer unacceptable distortion after welding to pipe. Size ... 92.1. 16. 3-1/2. 616.0. Size. Approximate piece weight in Kilograms. DN. NPS. Dimension as above. Involute splines. ANSI B92. 1a. 15 T. 16/32 DP 30". A. B. *). Weights and dimensions ... involute flanks (ANSI B 92.1a). Pressure angle 30". DRIVE SHAFTS. Ext. Involute Spline ANSI B 92.1 with major diameter modified. 13 teeth - 16/32 Pitch - 30 deg. Flat Root - Side fit - Class 5. SAE "B" SPLINE. 04. Drive shaft S, 22-4 (B) SAE J744 OCT 83. 7/8" dia. splined shaft; 30" pressure angle; 13 teeth; 16/32 Pitch; flat root; side fit; Fit class 5; ANSI B 92.1a-1976. A. B.

INLET PORT. ANSI B 92.1. 11T 16/32 SPLINE. FLAT ROOT SIDE FIT. 30" PRESSURE ANGLE. ZAHNWELLE ANSI B 92.1. 111 16/32 SP. FLAT ROOT SIDE FIT. 30 DN Blind flange with raised face. Pressure rating: Class 300; as per ANSI B16.5. ... 300; as per ANSI B16.5. Material: Forged. Grade F316L as per ASTM A182M. 30. ... 2.2.1 Dimensions of the flanges shall be as per ANSI B 16.5, details of which ... 92.1. 127. 19.05. 8. 3. 25 DN SDRF 300. 125. 15.9. 54. 25. 34.5. 50.8. 88.9. ... Unlike ANSI B92.1 splines DIN 5480 was structured to "permitt ... of 30". Involute splines in accordance with ANSI B92.2M and ISO 4156 are not interchangeable. ... customers' requirement. S30C/S40C. A151 1040. 1L. PU'RY. Blue. (B). 3.43. 1.6.86. S40C. ... Note: "H" dimension shows outside diameter of ANSI 150 lb flange. 10. 1 = ANSI B92.1-1970. 5 = SAE J500. 0.84375. 0.73071. 0.8750. 0.8758. 0.870. ... 16. (DS360 - External 30 deg DS361 - Internal 30 deg), 0.0508. 0.0500. N/A. 4156/ANSI B92.2M-.1980 and to compare it ... 30".37.50 or 45" pressure angle and are for the most part flank-fitting or ... United States as ANSI B92.1-1980. P30/31 in. 3.31. 3.25 mm. 84.1. 82.6. P50/51 in. 3.75. 3.62 mm. 95.3. 92.1. P75/76 in. 96 SAE 2 bolt "B" ANSI 101-2, type 2 (not available with O.B. bearing).

ansi

ansi, ansi encoding, ansi keyboard, ansi c, ansi code, ansi sql, ansible, ansible playbook, ansible tutorial, ansible template, ansi vs iso, ansi character set, ansible galaxy

Download PDF. Datasheet and "DXF ... B. Motor Half Coupling. SGEA51D02045FG. 1. C. Pump Half Coupling. ... 2200. 5500. 30. 450. 620. 850. 2500. 6100. 95. 120. 180. 550. 760. 2200. 620. 850. 2500 ... B.92.1-1970. Splined ... ANSI B92. 1A 1976. Shaft. DIN 5482. 0.5. 1. 2. G25 UNI 5007 Cast Iron - C40 Carbon Steel. A - 29T 5/10 DP 30" PA per ANSI B (Internal). E - N160 X ... B - 00.788/0.778 (14 Holes on 16 Hole Pattern) ... B - 36T 6/12 DP 30" PA per ANSI B92.1 (Internal). 25 - 30. * ANSI Forged Steel Check Valve. 31 - 33. * ANSI Dual Plate Check Valve. 34 - 35 ... S tem Nut. R retaining Nut. Nipple. H.W.Lock Nut. Handwheel. B ody. Bonnet. Wedge ... 92.1. 103.0. 8-28.5. 8-32. 8-35. 8-41. 12-38. 12-44.5. 461. 554. 659. 780. 904 ... tion types include manual, worm gear and, pneumatic or. 30.31. 32.33. 34. CONTENTS. Socket-Welding Type. 90-45 Elbow ... Dimensional Tolerances See ANSI B16.11 or JIS B2316. Size. Part No. M. B. D. A. C. ... 92.1. -, -, -, 0.14. 0.15. 0.27. 0.39. 0.47. 0.73. 1.25. 1.73. 3.30. 0.23. 0.36. 0.59. 0.73. Read Free Ansi B92 1 1970 Formulas For The Basic Dimensions 30 37 ... admin June 24, 2020 June 24, 2020 No Comments on ANSI B92 1 PDF Buy ANSI B ... b c e g h i k l kg. Weight and dimensions. SAE flange no. JPH 4 - 20. 20. 50. 102. 36. 19. 32 ... Involute splines. ANSI B92. 1a. 14 T 12/24. DP 30". Dimen- sions as above. Dimen- ... involute flanks (ANSI B 92.1a) ... Manual emergency operation. PVD-Beschichtung mit Genauigkeitsklasse B oder C ... Standards sind die Daten der Passverzahnungsnormen DIN 5480 (Deutschland), ANSI B92.1 (USA) und.

ansi keyboard

(6) Depth of Socket (Y) is covered by ANSI B16.5 only sizes through 3 inch, over 3 inch ... B. T1. T2. T3. A. R. Q. Diam. at Base of Hub. O. D. of. Raised. Face. Thick. ... 92.1. 101.6. 22.2. 25.4. 28.6. 30.2. 31.8. 38.1. 47.6. 50.8. 57.2. 63.5. 69.9. ... Sizes 14"(355.6mm) through 30"(762.0mm) are not at publication date covered. ... B. Subject to change -GP2_8002_1en_11/2015. Page 1 www.argo-hytos.com. Gear Pump - High ... ANSI B 92.1 11T - 16/32 DP. 23.1 (0.91). 14.2. (0.56). In American National Standard ANSI B92.1-1970 (R 1993), many features of the ... Basic Space Width is the basic space width for 30-degree pressure angle 1) ANSI B92.1a. 30" pressure angle, flat root, side fit, tolerance class 5. 2) Splines according to ANSI B92.1a, run out of spline is a deviation from standard. 3) Thread according to ... K68 flange ISO 3019-1 (SAE J744 - 101-2 (B)). Coupling for ... For max. wind speed please refer to lift chart in operator's cab or manual. 6. Working radii are ... ANSI B 30.5 and ISO 4305 Table 2. 9. The structures are ... 16/32 CLASS 5 SPLINE PER ANSI B 92.1 (MODIFIED). FITS 13 TOOTH 30" FLAT ROOT SIDE FIT 16/32 INTERNAL. SPLINES PER SAE J4986 CLASS OR ... B. Tsubaki RS Sprockets. Tooth wear rating. Hardnes s. Hardened layer depth distance ... This is the minimum tensile strength determined by ANSI Standard. ... 30. 32. 35. 40. 45. Note: 1. Please contact a Tsubaki representative prior to use of kW ... 92.1. 6.54. 7.66. 8.83. 10.1. 11.3. 12.7. 14.1. 15.5. 17.0. 18.5. 20.1. 21.7. 23.3.. WELDING NECK FLANGES, STD 150 Lbs. ANSI / ASME B 16.5. Dimensions are in mm. Cod. DN. O. C. X. A. K. Y. RF. R. B. STD. O. FORI. HOLES. N. FORI. B b. Improved Tsubaki Chain. "S" Chain load. "N" Number of times load is applied. Other ... 30. 32. 35. 40. 45. A - DRIVE CHAINS. A-6. RS25 1/4" Pitch. ANSI. Pitch. Bushing. Width ... 11.6 26.5 49.4 92.1 133 172 210 248 284 306 306 306 268 213 174 146 125 108 94.9 84.1. 30. 12.5 28.5 ... Manual lubrication. The oil is 27. EN 10241:2000. 28. FLANGES. Carbon steel ASTM A105 SAE 150lb. 30. ASA 300lb. 31 ... BUTTWELD FITTINGS - ASTM A234 WPB Welding Caps to ANSI B 16.9 ... 92.1. 93.7. 106.4. 117.5. 127.0. 139.7. Slip on screwed socket weld. 66.7.

ansi sql

English version BAUM catalogue ANSI-Your contacts-2018 ... standards. For more than 30 years, BAUM lined piping GmbH is a family-owned and ... 92.1. 120.7. 4.0. 23.5. 27.6. 33.4. 50.8. 79.4. 4.0. 18.7. 22.3. 4 x ¾". 4 x ¾". 7.1. 2". 1¼" ... Form B hor zontal. D fferent nom nal p pe s zes and total lengths on request. Vacuum B - Drive Chains. Standard Roller Chains. B-1. SU and H Series Chains. B-4 ... Single strand heavy series roller chain can be used with ANSI standard series roller chain sprockets of ... 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170. NUMBER ... n Type A: Manual or drip (Maximum chain speed 500 FPM)]. Pressure angle : 30°. Pitch Ø. : Ø41.275. Type of fit : Fillet root side. Per : ANSI B92.1-1996. Class 5. Paint free. Per SAE J744. Flange 152-4. Mounting flange.... according to DIN 5480, DIN 5482, ISO 4156, ANSI B92.2M, ANSI B92. 1. ... HTML and PDF format; Output of CAD data via eAssistant CAD plugins or DXF interface ... standards are also available, e.g., for ISO 4156 30" flat root or 30" fillet root. ... 30 S INVOLUTE SPLINE-INTERNAL. 14 TOOTH 12/24 PITCH. FLAT ROOT, SIDE FIT, CLASS 7. PER ANSI B92. 1-1970. TORQUE: 9-15 LBFT. /30. 132 www.hawe-inline.com. 02. 1. Overview: variable displacement axial ... 1) ANSI B 92.1, FLAT ROOT SIDE FIT, spline width deviating from the standard, s = 2.357-0.03 ... General operating manual for the assembly, initial operation and ... ANSI B16 VALVE FACE TO FACE DIMENSIONS. Inch. (mm) Inch ... 30. 33. 36. 39. 43. 45. 49. 53. 55. -----, 8 1/2. 9 1/2. 11 1/8. 12. 15 7/8. 16 1/2. 18. ... PER ANSI B92.1-1970. CLASS 5 .68 (17.27) MIN. FULL THD. 22" 30" ... 30" P.A. FLAT ROOT SIDE FIT SPLINE. PER ANSI B 92.1-1970. CLASS 5. 1.86. (47.4). INTERMEDIATE FLANGES. LVP 30. SAE "A" 2 HOLES. ASI. SAE J744 Jul88. Second pump side. ANSI B 92.1a-1976 class 6 - 9 teeth. 16/32 D.P. - ang=30°. Raised Face ANSI CLASS 150 Forged/Cast Steel Flanges. Raised Face ANSI ... 92.1. 60.5. 63.5. 25.4. 52.6. 62.0. 62.5. 2-1/2. 177.8. 22.2. 90.4. 104.8. 73.2. 69.9. 28.6 ... 30. 117.5. 7.9. 11.9. 0.8. -. 3. 3. 3. 3. -. 31. 123.8. 7.9. 11.9. 0.8 ... b d1. D d4. Blind d2 b f. Unit: mm. Pipe. Flange. Neck. Raised Face. Bolts. Arropx.. Pressure angle can be 30°, 37.5° or 45°. WN4 - Involute Splines - HEXAGON admin June 24, 2020 June 24, 2020 No Comments on ANSI B92 1 PDF Buy ANSI B ... 30. 450. 620. 850. 2500. 6100. 95. 120. 180. 550. 760. 2200. 620. 850. 2500. Half-coupling type. External diameter ... B.92.1.,1970. Splined bore as per standard pumps in the 4 series of B, F, N and G and as SILENCE gear pumps in the series ... ANSI B 92.1. 11T 16/32 SP ... service life. 20. Rectangular flange. 30. Rectangular flange. *) Dimension of Series 2 ... receive a project drawing (PDF format) if. Nominal. Pipe Size. Outside. Diameter. Center to Face. Inch. mm. D. A. B. N. E. F. G. R. ... 30. 5.549. 7.065. 6.118. 31. 5.925. 7.544. 6.533. 32. 6.313. 8.038. 6.961. 33 ... 92.1. 104.8. 127.0. 157.2. 185.7. 215.9. 269.9. 323.8. 381.0. 412.7. 469.9.. SAE was only 30"PA. B92.1-19xx also covered 37½" & 45" splines, formerly 45", were referred as "Serrations". So you need type of Dimensions 30 37 Download Pdf , Free Pdf Ansi B92 1 1970 Formulas For The .04 (113.54 1.02) , per ansi b 92.1-1970 class 6.075 r (1 . Involute Splines: According to DIN 5480 or ANSI B92.1 ... 30. 32. 8.0. 5. SNZT. HK2T. 5LST. SN5LTR. K7T. For Tailor-made Gear, Rack and Spline Inserts.. ANSI B92.1 These splines or multiple keys are similar in form to internal and external involute gears. In general. ... Equations for Involute Spline Basic Dimensions ANSI B92.1-1970, R1993. Term. Symbol. 30 deg q/D. 37.5 deg q/D. 45 deg q/D. The output coupling is for a pump shaft of SAE "A" size with a 30o involute spline (per SAE std J-744 Oct 83), 9T and 16/32 D.P. (Per ANSI B 92.1a1976). Con-... 16.28 / Mss Sp-43. Dimensions of Butt Welding Fittings To ANSI B 16.9 (upto 48")/ 11 ... Standard Finish Standard Finishes For Face Of Flange (ANSI B16.5) 30 ... 92.1. 104.8. 127.0. 157. 2. 11.1. 12.7. 14.3. 15.9. 17.5. 19.0. 21.33. 26.67. 33.40. ANSI B92.1. Profil. Abmessung. (P/Ps Teeth) a. Räumkapazität. Vorbohrung. [mm]. ANSI B92.1. 12/24 Z=17. 30". 32-80 mm. 33.70 G9. ANSI B92.1. 12/24 Z=14. 31.5E0.4. 8E0.5. ANSI B 92.1. 11T 16/32 SP. 30A pressure angle. Ø20 ... 0.33. P. 1.5. 4x6.5. DIN 6888. DIN 934.. M14x1.5-8-A. DIN 128-A14-FSt. = 70*10 Nm. PDF icon datasheet_mkl.pdf. Electromagnetic Single-Face Diaphragm Clutch. Einfächens-Systeme ... Anschluss Welle: SAE 20/40. 26 Zähne. 30°. ANSI B 92.1. Spline shaft: 14 teeth, 24/48 pitch, 30" pressure angle, coupling tolerance 5 as per ANSI B.92.1, confirming with NEMA 4". Submersible Revinvable Motor. Spline shaft: 13 teeth, 16/32 pitch, module 1.5875, 30" pressure angle, coupling tolerance 5 as per ANSI B.92.1, confirming with NEMA 6". 72/77 - 73.03 6.5. 30" INVOLUTE SPLINE-INTERNAL. 13 TOOTH 8/16 PITCH. FLAT ROOT, SIDE FIT, CLASS 7. PER ANSI B92. 1-1970. PART NUMBER. 13-547-458. NPI OR ... 29. SAE hDrAuLic. Pump SIAnDaRd. 30. SAE engine flyWheel houSing AnD. nAting houSing lAnGes. 32. ... nSi b 92.1-30" involute SPline. fLat root. side fit. 30 P.A. FLAT ROOT SIDE FIT SPLINE. PER ANSI B 92.1-1970. CLASS 5. INVOLUTE SPLINES. 2131. T ab le 2. F orm u ... S, but not higher than 30 psi (2 bar) absolute. 5. Table of values ... Hub for splined shaft to ANSI B.92.1a-1976 5/8 in 9T 16/32 DP. 1) (SAE J744 - 16-4 (A)). HV30 for rings, plugs and measuring pins and of 800 minimum HV30 ... 22.141/NF E 22.144/NF E 22.145. DIN 5480/ANSI B 92.1. Automatic measurement cycles, semi-automatic, manual : from a attribute gauge to a fully automated special ... h. Mating bolt. Inserted Flat. QTY Screw. DN50. PNI.64MPa 165. 125. 48.3. 57. 102.3+0.5. 20. 4. M16 ... 92.1.6.35.31.75. 8. M18. DN 2". (ANSI B ... 30. 8. M18. (ANSI B 16.5RF). 300psi. 255. 200. 89. 89. 57. 34+0.5. 32. 8. M18. ZHYQ Sensor & ... 4.5 USA spline standard ANSI B 92.1. 1.0 h. 4.6 International standard ISO. 27 Jul 2018. Dimensions 30 37 Download Pdf , Free Pdf Ansi B92 1 1970 Formulas ... Displacement up to 30 cm3 (1.83 inch3) • pmax 300 bar (4350 PSI) • Speed from 400 to ... 30 (1.18). DH. Max. 100 Nm. (73.8 lbf.ft). ANSI B 92.1 11T - 16/32 DP - IMP. ANSI 2.000". 2.250". HYD.SAE C SPLINE. 94/50006. 14. 30mm. 2 MODULE INV ... root fit shafts. Imperial involute splines are to ANSI B92.1-1970 Class 5. Excluding the 11-kW, 22-kW, and 30-kW models with a gear ratio of 1/10 in the GM-LJP series and the ... B. R. H. Parallel shaft type. LGM-SP Series (for uniform loads). Gearsed motor ... manual release brakes are designed only for indoor use. ... 92.1. 111. 145. 180. 217. 268. 349. 349. 1960. 2205. 2450. 2597. 2744. 3038.. 71 100 140. Pressure port B and suction port P: SAE ports at opposite sides O ... on cold start. (p ≤ 435 psi/30 bar, n ≤ 1000 rpm, tmin = -13 °F/-25 °C) ... Hub for splined shaft to ANSI B.92.1a-1976 5/8 in 9T 16/32 DP1) (SAE J744 - 16-4 (A)). S, but not higher than 30 psi (2 bar) absolute. 4. Direction of flow : (S ... Hub for splined shaft to ANSI B92.1a-1976 5/8 in 9T 16/32 DP. 1) (SAE J744 - 16-4 (A)). 16/32 pitch, 30" pressure angle, per ANSI B-92.1-1970. 53.19. [2.094]. 106.38. [4.188] ... pumps. Refer to the Heavy Duty Application manual (no. 5-401) for. DATA PER ANSI 92.1 - 1970. FLAT ROOT SIDE FIT, CLASS 5 FIT. NO. TEETH. 9. SPLINE PITCH. 20/40. PRESSURE ANGLE 30. SAE "AA" MOUNT - SPLINE B. 18009. S xxxx. Ordering code. External gear units Single pumps "SILENCE". Function ... ANSI B 92.1 ... 30. 45. 50. 55. 60. 65. 70. 75 te [rpm]. L. pA. [d. B. (A)]. V = 20 cm3/U rev n [rpm]. L. pA. [d. B. ... receive a project drawing (PDF format) if. -0.025. 9.5. ±0.1. 41. ±0.4. Min. 23 usable shaft length. Ø2. 1. 806. -0.127. Ø22. -0.1. ANSI B 92.1. 11T 16/32 DP. 30" pressure angle. N. D. P. Front cover. B. C.. ANSI-B-92.1/76. 30 16/32-DP. 11T FL. AT. Apr 1, 2016 . ASTM (ASTM International). assignments; or (b) holds no SC TAG assignments. 92.1.. Paper size standards govern the size of sheets of paper used as writing paper, stationery, cards ... On a sheet of paper, let a be the long side and b be the short side. ... For example, ANSI A is less elongated than A4, while ANSI B is more ... An intermediate size between Arch C and D with a long side of 30 inches (760 mm) usable shaft length. ANSI B 92.1. ... 30. 25. 20. 12/28. Bosch Rexroth AG Hydraulics. AZPJ RE 10 094/05.12 ... a pro ject drawing (PDF format) if a con- figuration for manual measurement and evaluation. Probe analogue for ... Ursula Chwalka. 09187/9522-30 uc@frenco.de ... 4.5 USA spline standard ANSI B 92.1. 1.0 h.. LVP 30. ANSI B 92.1a-1976 class 5 - 13 teeth. 16/32 D.P. - ang=30" flat root - side fit. SAE "B" STRAIGHT. 32. Available with flange code S5. STRAIGHT Ø 22. ... Local, manual configuration possible with closed housing ... diameter or standard (DIN. ANSI Schedule 10/40/80 etc.) will avoid the ... to B or D • Vertical pipeline: install according to A. Pressure and temperature transmitters are to be ... 92.1. 24. CI 300. 52.6. 8 x 19. 24. CI 150. ANSI. Sch. 80. 49.2. 4 x 19. 24. CI 300. 49.2. ... 23 TOOTH. 8/16 PITCH. 30" P.A. SIDE FIT. SPLINE. PER ANSI. B92.1-1970 ... 30". 15". FRAME MOUNT HOLES. 5/8-11 UNC-2B THD. 1, 10 (27.94) MIN.. S, but not higher than 30 psi (2 bar) absolute. 5. ... Hub for splined shaft to ANSI B.92.1a-1976 5/8 in 9T 16/32 DP ... Variety of manual and compensating. different flanges according to ISO 3019-1 and shafts according to ANSI B 92.1 with 9T, 13T or 15T gearing. ... In fits of water pump motors. ENGIRO supplies motors up to 30 kW rated power. ... 1. Data sheet 159AH_06020_BCR (PDF).. Dimensions 30 37 Download Pdf , Free Pdf Ansi B92 1 1970 Formulas For The .04 (113.54 1.02) , per ansi b 92.1-1970 class 6.075 r (1 . 30 S INVOLUTE SPLINE-INTERNAL. 14 TOOTH 12/24 PITCH. FLAT ROOT, SIDE FIT, CLASS 7. PER ANSI B92. 1-1970. TORQUE: 9-15 LBFT.. Ansi B92 1 1970 Formulas For The. Basic Dimensions 30 37 pdf free ansi b92 1 1970 formulas for the basic dimensions 30 37 manual pdf pdf file. Page 1/15 ... "B" "A". 30 minimum. Null position. Torque applied to control handle shaft ... Manual displacement control handle ... ANSI B92.1-1970, class 6.. ANSI B92.1a. □ □. 2. 10. Anschlüsse ... B. 11. Zusatzausrüstung. Ohne Anbauten. □. □. □. 0. Mit Ladepumpe (Injektor). □. □. 1. 12. ... Betriebsdruckbereich: pHDMin ≥ http://pfcs.com/aiwlwlc-45565b?e23 In American National Standard ANSI B92.1-1970 (R 1993), many features of the ... ANSI B92.1-1970 SAE□□□□□ □ INVOLUTE SPLINES 2129 Form ... 2133 Min Effective Space Width (BASIC). Sv min 30 deg φ 37.5 deg φ 45 ... B. Subject to change -GP2_8002_1en_11/2015. Page 1 www.argo-hytos.com. Gear Pump - High ... 30.96. 35.25. 43.71. [GPM]. 1.43. 1.70. 2.14. 2.92. 3.54. 4.37. 5.96. 7.45. 8.18. 9.31. 11.55 ... ANSI B 92.1 11T - 16/32 DP. 23.1 (0.91). 14.2.. 16/32 pitch, 30" pressure angle, per ANSI B-92.1-1970. 53.19. [2.094]. 106.38. [4.188] ... pumps. Refer to the Heavy Duty Application manual (no. 5-401) for. the catalog and instruction manual carefully. If you find ... B. BS Roller Chain (ANSI-B Type). 107. DID. BF.DID. BFH. BF Bushing Chain. 298. DID. ... 23. 24. 25. 28. 30. 32. 35. 40. 45. RJ. No. of. Teeth of. Small Sprocket. Type of Lubrication ... 92.1. 8.83. 10.1. 11.4. 12.7. 14.1. 15.5. 17.0. 18.5. 20.1. 21.7. 23.3. 25.0. 26.7. 28.5.. включает 4 конусных шпиней пгaa B, F, N и G. a racke v ... ANSI B 92.1. 9T 16/32 SP ... 304/1. Minn. 10.6. 14.3. ±0.1. 15.7. ±1. 7.2401. Hacco bez uloznjenja naia. cm. cr. pr. 0522. ... поулици череп-предложење (a PDF форма). Made to ANSI B-29.1 specifications. Available in sizes #35 - 30. 40. 10". 10". 4.4. 50". 22.8. 100". 45. 10". 8.8. 10". 12.4. 10". 17.1. 50. 5/8". 10". 7.1. 50". 37.8. ... to ANSI B92.1-1970. Pressure angles on all involute splines listed are 30 degrees. Spline OD's as listed for shafting, subwelds and nibs is the form diameter. This is the minimum tensile strength determined by ANSI Standard. If a roller ... According to the former JIS B 1801-1997, the maximum allowable load indicates a ... 30. 16. 88. 25. 38.00. 40.5. 8. 20. 32. 16. 100. 26. 39.51. 42.0. 10. 22. 33. 16 ... 92.1. 6.54. 7.66. 8.83. 10.1. 11.3. 12.7. 14.1. 15.5. 17.0. 18.5. 20.1. 21.7. 23.3.. size. DIN 5482.1 ANSI B 92.1 e9 (SAE) 0 = 30". 148 100 B25 x 22. 50 150 100 B 30 x 27. 75 170 115 B 35 x 31. 105 184 125 B 40 x 36. 140 200 140 B 45 x 41. cfec45ec80